To remove a concrete sealer using a liquid cleaner, you need a specialized chemical stripper or solvent rather than a standard floor soap. Top options include Prosoco Cure & Seal Remover, Klean-Strip Liquid Concrete Stripper, or solvent-based removers like Xylene for acrylics. Prosoco +3

Choosing the Right Liquid Cleaner

- **Film-Forming/Acrylic Sealers:** Use a citrus or soy-based stripper, or a solvent like Xylene which melts the acrylic back into a liquid state. Concrete Decor Magazine
- **Cure and Seal Products:** Heavy-duty commercial strippers break the bonds of high-solids sealants so they lift off the masonry. Prosoco
- **Penetrating Sealers:** Liquid chemical strippers usually do not work on deep penetrating sealers; those typically require mechanical grinding.

Steps to Strip Concrete Sealer

- **Test a small area:** Pick a hidden corner to verify the chemical reacts correctly with your specific sealer.
- **Apply the liquid:** Pour, roll, or spray the stripper evenly across the floor.
- **Let it dwell:** Allow the product to sit and soften the coating for 15 to 30 minutes, making sure it does not dry out.
- **Agitate and scrub:** Use a stiff-bristle nylon brush to loosen the gummy residue.
- **Rinse or extract:** Wash away the liquefied old sealer using a pressure washer or capture the waste with a wet vacuum. The Home Depot +2